

# **VEGAVIB 62**

# **Contactless electronic switch**

# Vibrating level switch with suspension cable for granuled bulk solids



### **Application area**

The VEGAVIB 62 is a level switch for granular and coarse-grained bulk solids. The optimized rod design without corners and edges avoids jamming of the bulk solids and is easy to clean. The VEGAVIB 62 detects reliably and accurately the min. or max. level in bulk solids. The position of the switching point is specified flexibly through the length of the suspension cable.

### Your benefit

- Minimum time and cost expenditure due to simple setup without medium
- Reliable function due to product-independent switching point
- Low maintenance costs

# Function

The vibrating rod of VEGAVIB 62 is energized by a piezo drive to vibrate at its resonance frequency. If the medium covers the vibrating rod, the amplitude is damped. The electronics detects this change and converts it into a switching command. A reliable function in granulated bulk solids is ensured by the ideal rod design.

#### Technical data

Process pressure -1 ... +6 bar/-100 ... +600 kPa

(-14.5 ... +87 psig)

 $\begin{array}{ll} \mbox{Process temperature} & -40 \ ... \ +150 \ ^{\circ}\mbox{C} \ (-40 \ ... \ +302 \ ^{\circ}\mbox{F}) \\ \mbox{Density} & > 0.02 \ \mbox{g/cm}^{3} \ (0.0007 \ \mbox{lbs/in}^{3}) \\ \end{array}$ 

Ambient temperature on the housing

-40 ... +80 °C (-40 ... +176 °F)

and modeling

Storage and transport

Switching delay

-40 ... +80 °C (-40 ... +176 °F)

temperature

Hysteresis

approx. 2 mm (0.08 in) with vertical instal-

lation

Process fitting Threads from G1, 1 NPT, flanges from

DN 32, 11/2", hygienic fittings

Operating voltage 20 ... 253 V AC, 50/60 Hz, 20 ... 253 V DC

Load current min. 10 mA/max. 400 mA

When being covered: 0.5 s, when being uncovered 1 s

SIL qualification Optionally up to SIL2

#### **Materials**

The wetted parts of the instrument are made of stainless steel 316L. The suspension cable is made of PUR or FEP. The supplied process seal is made of Klingersil C-4400.

You will find a complete overview of the available materials and seals in the "configurator" on our homepage at <a href="https://www.vega.com/configurator">www.vega.com/configurator</a>.

## **Housing versions**

The housings are available in plastic, stainless steel or Aluminium. They are available with protection ratings up to IP 67.

### **Electronics versions**

The instruments are available in different electronics versions. Apart from the versions with transistor output, contactless electronic switch and relay output, a two-wire version for connection to a signal conditioning instrument and a NAMUR version are also available.

# Approvals

The instruments are suitable for use in hazardous areas and are approved, for example, according to ATEX, FM, CSA and IEC. You can find detailed information on the existing approvals in the "configurator" on our homepage at <a href="https://www.vega.com/configurator">www.vega.com/configurator</a>.



Thorne & Derrick


DERRICK +44 (0) 191 490 1547

WWW.heatingandprocess.com



### Operation


The mode and sensitivity of the level switch can be adjusted on the electronics module. A signal lamp shows the switching status of the instrument.



Electronics and connection compartment - contactless electronic switch

- 1 Potentiometer for switching point adaptation
- DIL switch for mode adjustment
- Ground terminal 3
- Connection terminals
- Control lamp

### **Electrical connection**




## Wiring plan

1 Voltage supply

You can find details on electrical connection in the instrument operating instructions on our homepage at www.vega.com/downloads.

### **Dimensions**



- Version with PUR suspension cable
- Version with FEP suspension cable

## Information

You can find further information on the VEGA product line on our homepage www.vega.com.

In the download section under www.vega.com/downloads you'll find free operating instructions, product information, brochures, approval documents, instrument drawings and much, much more.

# Instrument selection

With the "Finder" at www.vega.com/finder and "VEGA Tools" you can select the most suitable measuring principle for your application. You can find detailed information on the instrument versions in the "Configurator" at www.vega.com/configurator and "VEGA Tools".

# Contact

You can find the VEGA agency serving your area on our homepage www.vega.com.



THORNE & Thorne & Derrick

DERRICK +44 (0) 191 490 1547

INTERNATIONAL www.heatingandprocess.com