



# LFP0600-B4NMB

LFP Cubic



LEVEL SENSORS

Thorne & Derrick  
+44 (0) 191 490 1547  
[www.heatingandprocess.com](http://www.heatingandprocess.com)

**SICK**  
Sensor Intelligence.



Illustration may differ



IO-Link



### Ordering information

| Type          | Part no. |
|---------------|----------|
| LFP0600-B4NMB | 1057096  |

Other models and accessories → [www.sick.com/LFP\\_Cubic](http://www.sick.com/LFP_Cubic)

### Detailed technical data

#### Features

|                            |                    |
|----------------------------|--------------------|
| <b>Medium</b>              | Fluids             |
| <b>Measurement</b>         | Switch, Continuous |
| <b>Design</b>              | Standard           |
| <b>Probe type</b>          | Mono rod probe     |
| <b>Probe length</b>        | 600 mm             |
| <b>Process pressure</b>    | -1 bar ... 10 bar  |
| <b>Process temperature</b> | -20 °C ... +100 °C |
| <b>GOST approval</b>       | ✓                  |
| <b>RoHS certificate</b>    | ✓                  |
| <b>IO-Link</b>             | ✓                  |
| <b>CULus certificate</b>   | ✓                  |

#### Performance

|                                         |                                                                |
|-----------------------------------------|----------------------------------------------------------------|
| <b>Accuracy of sensor element</b>       | ± 5 mm <sup>1)</sup>                                           |
| <b>Repeatability</b>                    | ≤ 2 mm                                                         |
| <b>Resolution</b>                       | < 2 mm                                                         |
| <b>Response time</b>                    | < 400 ms                                                       |
| <b>Dielectricity constant</b>           | ≥ 5 for mono rod probe / rope probe<br>≥ 1.8 with coaxial tube |
| <b>Conductivity</b>                     | No limitation                                                  |
| <b>Maximum level change</b>             | ≤ 500 mm/s                                                     |
| <b>Deactivated area at end of probe</b> | 10 mm <sup>1)</sup>                                            |

<sup>1)</sup> With water under reference conditions.

|             |                              |
|-------------|------------------------------|
| <b>MTTF</b> | 194.3 years (EN ISO 13849-1) |
|-------------|------------------------------|

<sup>1)</sup> With water under reference conditions.

## Electronics

|                              |                                                                                                                                                         |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Supply voltage</b>        | 12 V DC ... 30 V DC <sup>1)</sup>                                                                                                                       |
| <b>Power consumption</b>     | ≤ 100 mA at 24 V DC without output load                                                                                                                 |
| <b>Initialization time</b>   | ≤ 5 s                                                                                                                                                   |
| <b>Protection class</b>      | III                                                                                                                                                     |
| <b>Electrical connection</b> | Round connector M12 x 1, 5-pin                                                                                                                          |
| <b>Output signal</b>         | 4 mA ... 20 mA, 0 V ... 10 V automatic switching depending on the load., 1 PNP transistor output (Q1) and 1 PNP / NPN transistor output (Q2) switchable |
| <b>Output load</b>           | 4 mA ... 20 mA < 500 Ohm at U <sub>v</sub> > 15 V, 4 mA ... 20 mA < 350 Ohm at U <sub>v</sub> > 12 V, 0 V ... 10 V > 750 Ohm at U <sub>v</sub> 14 ≥ V   |
| <b>Hysteresis</b>            | Min. 2 mm, free adjustable                                                                                                                              |
| <b>Signal voltage HIGH</b>   | V <sub>s</sub> - 2 V                                                                                                                                    |
| <b>Signal voltage LOW</b>    | ≤ 2 V                                                                                                                                                   |
| <b>Output current</b>        | < 100 mA                                                                                                                                                |
| <b>Inductive load</b>        | < 1 H                                                                                                                                                   |
| <b>Capacitive load</b>       | 100 nF                                                                                                                                                  |
| <b>Enclosure rating</b>      | IP 67: EN 60529                                                                                                                                         |
| <b>Temperature drift</b>     | < 0.1 mm/K                                                                                                                                              |
| <b>Lower signal level</b>    | 3.8 mA ... 4 mA                                                                                                                                         |
| <b>Upper signal level</b>    | 20 mA ... 20.5 mA                                                                                                                                       |
| <b>EMC</b>                   | EN 61326-2-3, 2014/30/EU                                                                                                                                |

<sup>1)</sup> All connections are polarity protected. All outputs are overload and short-circuit protected.

## Mechanics

|                           |              |
|---------------------------|--------------|
| <b>Wetted parts</b>       | 1.4404, PTFE |
| <b>Process connection</b> | ¾" NPT       |
| <b>Housing material</b>   | Plastic PBT  |
| <b>Max.probe load</b>     | ≤ 6 Nm       |

## Ambient data

|                                      |                   |
|--------------------------------------|-------------------|
| <b>Ambient operating temperature</b> | -20 °C ... +60 °C |
| <b>Ambient storage temperature</b>   | -40 °C ... +80 °C |


## Classifications

|                     |          |
|---------------------|----------|
| <b>ECI@ss 5.0</b>   | 27371813 |
| <b>ECI@ss 5.1.4</b> | 27371813 |
| <b>ECI@ss 6.0</b>   | 27371813 |
| <b>ECI@ss 6.2</b>   | 27371813 |
| <b>ECI@ss 7.0</b>   | 27371813 |
| <b>ECI@ss 8.0</b>   | 27371813 |
| <b>ECI@ss 8.1</b>   | 27371813 |
| <b>ECI@ss 9.0</b>   | 27371813 |

|                       |          |
|-----------------------|----------|
| <b>ETIM 5.0</b>       | EC001447 |
| <b>ETIM 6.0</b>       | EC001447 |
| <b>UNSPSC 16.0901</b> | 41113710 |


### Dimensional drawing (Dimensions in mm (inch))

Dimensional drawing: mono rod probe




- ① M: measuring range
- ② L: Probe length
- ③ IA: Inactive area at process connection 25 mm (0.98")
- ④ IAE: Inactive area at probe end 10 mm (0.39")

## Connection type



- ① L<sup>+</sup>: Supply voltage, brown
- ② Q<sub>A</sub>: Analog current/voltage output, white
- ③ M: Ground, reference ground for current-/voltage output, blue
- ④ C/Q<sub>1</sub>: Switching output 1, PNP/IO-Link-communication, black
- ⑤ Q<sub>2</sub>: Switching output 2, PNP/NPN, grey


## Instruction for installation

**Mono rod probe mounted in metal tank**

M = Measuring range  
 X = Inactive area at probe end  
 No measurement possible








**Rope probe mounted in metal tank**

Installation in nozzle:  
 $D \geq \text{DN } 25 \text{ (1")}$   
 Distance tank wall/tank bottom:  
 $A \geq 50 \text{ mm (1.97")}$   
 Distance to other tank fittings:  
 $\geq 100 \text{ mm (3.94")}$



### Recommended accessories

Other models and accessories → [www.sick.com/LFP\\_Cubic](http://www.sick.com/LFP_Cubic)

|                                                                                     | Brief description                                                                                                             | Type               | Part no. |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|--------------------|----------|
| Flanges                                                                             |                                                                                                                               |                    |          |
|    | Process connection adapter G 3/4 to G1                                                                                        | BEF-HA-G1BSP1-LFP1 | 2067603  |
|    | Weld-in flange G 3/4"                                                                                                         | BEF-FL-GEWG34-LFP1 | 2082150  |
| Mounting brackets and mounting plates                                               |                                                                                                                               |                    |          |
|    | Mounting bracket, mounting hardware included                                                                                  | BEF-FL-304LFP-HLDR | 2077391  |
| Plug connectors and cables                                                          |                                                                                                                               |                    |          |
|    | Head A: female connector, M12, 5-pin, straight<br>Head B: cable<br>Cable: PVC, unshielded, 2 m                                | DOL-1205-G02M      | 6008899  |
|    | Head A: female connector, M12, 5-pin, straight<br>Head B: cable<br>Cable: drag chain use, PUR, halogen-free, unshielded, 2 m  | DOL-1205-G02MC     | 6025906  |
|   | Head A: female connector, M12, 5-pin, straight<br>Head B: cable<br>Cable: PVC, unshielded, 5 m                                | DOL-1205-G05M      | 6009868  |
|  | Head A: female connector, M12, 5-pin, straight<br>Head B: cable<br>Cable: drag chain use, PUR, halogen-free, unshielded, 5 m  | DOL-1205-G05MC     | 6025907  |
|  | Head A: female connector, M12, 5-pin, straight<br>Head B: cable<br>Cable: PVC, unshielded, 10 m                               | DOL-1205-G10M      | 6010544  |
|  | Head A: female connector, M12, 5-pin, straight<br>Head B: cable<br>Cable: drag chain use, PUR, halogen-free, unshielded, 10 m | DOL-1205-G10MC     | 6025908  |
|  | Head A: female connector, M12, 5-pin, angled<br>Head B: cable<br>Cable: PVC, unshielded, 2 m                                  | DOL-1205-W02M      | 6008900  |
|  | Head A: female connector, M12, 5-pin, angled<br>Head B: cable<br>Cable: drag chain use, PUR, halogen-free, unshielded, 2 m    | DOL-1205-W02MC     | 6025909  |
|  | Head A: female connector, M12, 5-pin, angled<br>Head B: cable<br>Cable: PVC, unshielded, 5 m                                  | DOL-1205-W05M      | 6009869  |
|  | Head A: female connector, M12, 5-pin, angled<br>Head B: cable<br>Cable: drag chain use, PUR, halogen-free, unshielded, 5 m    | DOL-1205-W05MC     | 6025910  |
|  | Head A: female connector, M12, 5-pin, angled<br>Head B: cable<br>Cable: PVC, unshielded, 10 m                                 | DOL-1205-W10M      | 6010542  |
|  | Head A: female connector, M12, 5-pin, angled<br>Head B: cable<br>Cable: drag chain use, PUR, halogen-free, unshielded, 10 m   | DOL-1205-W10MC     | 6025911  |

|                                                                                   | Brief description                                                                    | Type               | Part no. |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------|----------|
| Spare parts                                                                       |                                                                                      |                    |          |
|  | Spare probe for LFP Cubic, probe length 1000 mm, material 1.4404/316L, diameter 7 mm | BEF-ER-SN1000-LFPC | 2065700  |
|                                                                                   | Spare probe for LFP Cubic, probe length 2000 mm, material 1.4404/316L, diameter 7 mm | BEF-ER-SN2000-LFPC | 2065701  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations [www.sick.com](http://www.sick.com)



THORNE &  
DERRICK  
INTERNATIONAL

Thorne & Derrick  
+44 (0) 191 490 1547  
[www.heatingandprocess.com](http://www.heatingandprocess.com)

**SICK**  
Sensor Intelligence.