

Product Specification

Heating Jackets

LMK Thermosafe Ltd



Tel: +44 (0)191 490 1547
Fax: +44 (0)191 477 5371
Email: northernsales@thorneandderrick.co.uk
Website: www.heattracing.co.uk
www.thorneandderrick.co.uk

LMK Standard Heating Jackets Variations for 205 litre drums

Ref.	Circumference / Height	Nominal Capacity (Litres/Imp/USGal)	Nominal Power (240v)	Outer Material / Inner Insulation
D 2 strap style	1800 - 1950 mm / 440mm 71" – 76¾" / 17¼"	205/210 litres 45 Imp Gal 55 US Gal	450 W	Coated Nylon Needled Polyester
HHD 3 strap style	1800 - 1950 mm / 780mm 71" – 76¾" / 30½"	205/210 litres 45 Imp Gal 55 US Gal	1000 W	Coated Nylon & Custom coated glass cloth / Stitched fibre glass
HP2D 3 strap style	1800 – 1950 mm / 850mm 71" – 76¾" / 33½"	205/210 litres 45 Imp Gal 55 US Gal	1300 W	Silicone rubber coated glass-cloth / Stitched fibreglass



HJD



HHD



HP2D

Jackets are supplied with a 5 metre supply cable (2 x 1mm², PVC insulated, sheathed, galvanised steel wire braided) and an integral 0-90°C adjustable capillary thermostat.

-5-40°C thermostats and 110v versions are also available at no additional charge. A 0-180°C thermostat is also available for the High Power jacket.

Special or non-standard sizes available, please call with your container dimensions for a quotation.

