



## PNHT

### POWER CONNECTORS

- ▶ 240 °C
- ▶ 30 A / 500 V
- ▶ IP44

page 102



## DSHT

### POWER CONNECTORS

- ▶ 240° C and 400 °C
- ▶ 90 A / 690 V
- ▶ IP66

page 103



# RANGE HIGH TEMPERATURE

This range of power connectors and signal & control connectors, provides excellent connection quality even with high-temperature environments. Very robust, those connectors also resist to corrosion.

HIGH  
TEMPERATURE

Find all information on our website:



[marechal.com](https://www.marechal.com)



Technical documentation



Product configurator

# HT

## HIGH TEMPERATURE CONNECTORS

- ▶ FROM 30 TO 90 A
- ▶ FROM 240 TO 400 °C

### MAIN FEATURES

	PNHT	DSHT
Max. operating temperature steady	240 °C	240 °C / 400 °C (2h)
Rated current I <sub>n</sub>	30 A	90 A
U <sub>max</sub>	500 V	690 V
Maximum no. of contacts	3P+N+E	3P+E
Protection	IP44	IP66
Robustness	IK09	IK09
Flexible wiring (min-max)	1 - 6 mm <sup>2</sup>	*
Stranded wiring (min-max)	1,5 - 10 mm <sup>2</sup>	*

\* Armoured and unarmoured flexible cables, from 10 mm<sup>2</sup> up to 95 mm<sup>2</sup> via terminals box side and 6 mm<sup>2</sup>, 16 mm<sup>2</sup> & 35 mm<sup>2</sup> via crimping contacts plug side.

### PNHT (30 A) 240 °C

SOCKET-  
OUTLET  
female



INLET  
male



Voltage 50 Hz	Polarity	Part no. 240 °C	Part no. 240 °C
20 - 24 V	2P	092408A185	092808A185
190 - 230 V	3P+E	0924033185	0928033185
220 - 250 V	1P+N+E	0924015185	0928015185
380 - 440 V	3P+E	0924013185	0928013185
380 - 440 V	3P+N+E	0924017185	0928017185

**BOXES**  
Cable gland  
not included



Straight metal



Straight metal +  
inclined metal 45°

**SLEEVE**



Inclined  
metal 45°

**HANDLE**



Straight  
metal

Entry					
M20	092A055185	092A653185	092A027185	6-13 mm	092A963185
M25		092A672185		10-18 mm	092A674185
M32		092A673185		16-24 mm	092A675185



### SPECIFICATION

High temperature connectors, silver butt-contacts with metal braid, Automatic IP44.

**DSHT (90 A)**  
**240 °C \***



**WALL  
MOUNTING  
SOCKET**

**PLUG**

Voltage 50 Hz	Polarity	Part no.	Part no.
380 - 440 V	3P+E	3934013Zxxxx	3938013Zxxxx

\* 400 °C for 2 hours, see range BOXES AND OTHER PRODUCTS, Equipment for tunnels.  
Please contact us for configurations and Part No.



**THORNE &  
DERRICK**  
**INTERNATIONAL**

**Thorne & Derrick**  
+44 (0) 191 410 4292  
[www.heatingandprocess.com](http://www.heatingandprocess.com)