

TYPICAL CONFIGURATION



MAIN FEATURES

Rated current/contact (wiring according to standard)	25 A	Ambient temperature	-40 °C to +60 °C
Σ of currents (contacts)	≤ 350 A	Flexible wiring (min-max)	1 - 6 mm ²
Maximum voltage	415 V	Stranded wiring (min-max)	1,5 - 10 mm ²
IP protection lid closed	IP55	Wiring (terminals)	screw-type
IP protection connected plug	IP54	Keying positions	4
Shock resistance	IK09		

**SOCKET-
OUTLET** female
DN20c (25 A)



INLET male
DN20c (25 A)



Umax	Polarity	Part no.	Part no.
50 V	10P	1964100	1968100
50 V	11P	1964110	1968110
50 V	12P	1964120	1968120
50 V	13P	1964130	1968130
50 V	14P	1964140	1968140
50 V	15P	1964150	1968150
50 V	16P	1964160	1968160
50 V	17P	1964170	1968170
50 V	18P	1964180	1968180
50 V	19P	1964190	1968190
50 V	20P	1964200	1968200
415 V	9P+E	1964091	1968091
415 V	10P+E	1964101	1968101
415 V	11P+E	1964111	1968111
415 V	12P+E	1964121	1968121
415 V	13P+E	1964131	1968131
415 V	14P+E	1964141	1968141
415 V	15P+E	1964151	1968151
415 V	16P+E	1964161	1968161
415 V	17P+E	1964171	1968171
415 V	18P+E	1964181	1968181
415 V	19P+E	1964191	1968191

Note: When using two different voltages on the same site, thank you for contacting us.



**THORNE &
DERRICK
INTERNATIONAL**

Thorne & Derrick
+44 (0) 191 410 4292
www.heatingandprocess.com

MULTI

BOXES

Cable gland
not included



Wall box metal +
inclined metal 70°

Wall box metal +
inclined metal 30°

Wall box metal +
straight metal sleeve

Entry			
M32	879A823419	196A653419	196A095419
M40	879A823420	196A653420	196A095420
M50	879A823	196A653	196A095
M63	879A823463	196A653463	196A095463

SLEEVES



Inclined
metal 30°

Inclined
metal 70°

Straight
metal

196A027	879A087	196A127
---------	---------	---------

HANDLES*



Straight
elastomer

Straight poly with
metal cable gland

Straight metal
with metal cable
gland

Straight poly
without cable
gland with metric
threaded entry

18-25 mm	659A013D25	35-48 mm	619A25363M	16-24 mm	196A95332M	M63	619A253463
25-35 mm	659A013D35			22-32 mm	196A963		
35-45 mm	659A013D45			34-44 mm	196A95350M		

* For use at 135 °C, use only metal handles.

ACCESSORIES & OPTIONS

Locking with shaft for 3 padlocks
ø 8 mm (padlocks not supplied)

Socket no. + 844

Lockable plug: contact us

Padlocking device 1 to 6 padlocks
873A541



E-Stop button

Socket no. + 453



Inlet cap

196A126



Closing mechanism

Draw lever only: 196A376

Draw plate only: 196A396



180° opening lid

Self-returning lid

180° opening and self-returning lid
IP66/IP67 (socket & inlet)

Socket no. + 10

Socket no. + R

Socket no. + 18

Socket no. + 600