

TYPICAL CONFIGURATION



WALL MOUNTING SOCKET DN9c



PLUG DN9c



Wall box metal 20°
191A053



Socket-outlet
1914081



Straight handle poly
191A013



Inlet
1918081

MAIN FEATURES

Rated current/contact (wiring according to standard)	30 A	Ambient temperature	-40 °C to +60 °C
Σ of currents (contacts)	≤ 210 A	Flexible wiring (min-max)	1 - 6 mm ²
Maximum voltage	415 V	Stranded wiring (min-max)	1,5 - 10 mm ²
IP protection lid closed	IP55	Wiring (terminals)	screw-type
IP protection connected plug	IP54	Keying positions	2
Shock resistance	IK09		

**SOCKET-
OUTLET** female
DN9c (30 A)



INLET male
DN9c (30 A)



Note: When using two different voltages on the same site, thank you for contacting us.

Umax	Polarity	Part no.	Part no.
50 V	6P	1914060	1918060
50 V	7P	1914070	1918070
50 V	8P	1914080	1918080
50 V	9P	1914090	1918090
415 V	5P+E	1914051	1918051
415 V	6P+E	1914061	1918061
415 V	7P+E	1914071	1918071
415 V	8P+E	1914081	1918081

AUXILIARY CONTACTS

Including 2 pilot contacts (30 A)
Including 2 pilot contacts (30 A)

Socket no. + 262
Inlet no. + 262

Including 4 pilot contacts (30 A)
Including 4 pilot contacts (30 A)

Socket no. + 264
Inlet no. + 264



BOXES

Cable gland
not included



Wall box metal 20°



**Wall box metal +
inclined metal 70°**



**Wall box metal +
inclined metal 30°**



**Wall box metal +
straight metal sleeve**

Entry				
M20	191A053	873A053417	191A653	191A095
M25	191A053418	873A053	191A653418	191A095418
M32	191A053419	873A053419	191A653419	191A095419
M40		873A053420	191A653420	191A095420

SLEEVES



**Inclined
metal 30°**



**Inclined
metal 70°**



**Straight
metal**

191A027	873A087	191A127
---------	---------	---------

HANDLES



Straight poly



**Straight poly with
poly cable gland**



**Straight metal
with metal cable
gland**



**Straight poly
without cable
gland with metric
threaded entry**

10-30 mm	191A013	5-12 mm	191A753	7-13 mm	191A963	M20	191A253417
10-30 mm	191A473*	9-18 mm	191A25325P	8-16 mm	191A95325M	M25	191A253418
		14-25 mm	191A25332P	16-24 mm	191A95332M	M32	191A253419
		18-32 mm	191A25340P	22-32 mm	191A95340M	M40	191A253420

*With built-in finger draw plate (recommended for inline connections)

ACCESSORIES & OPTIONS

**Locking with shaft for 3 padlocks
ø 8 mm (padlocks not supplied)**

Socket no. + 844

Lockable plug: contact us

**Padlocking device 1 to 6 padlocks
873A541**



E-Stop button

Socket no. + 453



Inlet cap

191A126



180° opening lid

Self-returning lid

**180° opening and self-returning lid
IP66/IP67 (socket & inlet)**

Socket no. + 10

Socket no. + R

Socket no. + 18

Part no. + 600