

TYPICAL CONFIGURATION

WALL BOX DX3

Wall box 90°
26 3A B53

Socket-outlet
26 34 017

PLUG DX3

Plug
26 31 017

MAIN FEATURES

Rated current (with wiring according to standard)	32 A	Flexible wiring (min-max)	2,5 - 10 mm ²
Maximum voltage	750 V	Stranded wiring (min-max)	2,5 - 10 mm ²
IP protection lid closed	IP65	Other wiring	on request
IP protection connected plug	IP65	Keying positions	12
Shock resistance	IK10	Protection mode	de
Ambient temperature	-25 °C to +60 °C	ATEX zones	1 & 2, 21 & 22

EACH SOCKET OUTLET OR INLET MUST BE ASSOCIATED WITH A BOX, A SLEEVE OR A HANDLE.

SOCKET-OUTLET female
DX3 (32 A)



INCLINED APPLIANCE INLET male
DX3 (32 A)



PLUG male
DX3 (32 A)



Voltage 50 Hz	Polarity	Part no.	Part no.	Part no.
220 - 250 V	1P+N+E	2634015	2636015	9-16 mm 2631015
380 - 440 V	3P+E	2634013	2636013	9-16 mm 2631013
380 - 440 V	3P+N+E	2634017	2636017	9-16 mm 2631017

► Other voltages, frequencies and contact configurations are available (see page 10).

BOXES

Ex metal cable gland included*



Wall box metal 90°

HANDLES

Ex metal cable gland included*



Straight handle metal

Cable gland entry	Part no.	Cable gland entry	Part no.
M20	263AB5320M 8-13 mm	M20	263A95320M 8-13 mm
M25	263AB53 9-16 mm	M25	263A963 9-16 mm
M32	263AB5332M 12-21 mm	M32	263A95332M 12-21 mm

* For alternatives with Earth continuity, please contact us

LOCKING

Locking position connected or disconnected by lockable shaft as standard.

MARECHAL ELECTRIC MAROMME

II 2 G D Ex de IIC tD A21
 -25 °C ≤ Ta ≤ +60 °C T5 T84 °C
 -25 °C ≤ Ta ≤ +50 °C T6 T74 °C
 IECEx LCI 09.0014 / LCIE 05 ATEX 6127