



WALL MOUNTING SOCKET PN7c



PLUG PN7c



Wall box poly 30°
01NA053



Socket-outlet
01P4061



Straight handle poly
01NA013



Inlet
01P8061

MAIN FEATURES

Rated current/contact (wiring according to standard)	25 A
Σ of currents (contacts)	≤ 130 A
Maximum voltage	500 V
IP protection lid closed	IP66/IP67
IP protection connected plug	IP66/IP67
Shock resistance (poly casing)	IK08

Shock resistance (metal casing)	IK09
Ambient temperature	-40 °C to +60 °C
Flexible wiring (min-max)	1 - 4 mm ²
Stranded wiring (min-max)	1 - 6 mm ²
Wiring (terminals)	screw-type
Keying positions	5

SOCKET-
OUTLET female
PN7c (16/25 A)
GRP



INLET male
PN7c (16/25 A)
GRP



Umax	Polarity	Part no.	Part no.
50 V	5P (25 A)	01P4050	01P8050
50 V	6P (16 A)	01P4060	01P8060
50 V	7P (16 A)	01P4070	01P8070
500 V	4P+E (25 A)	01P4041	01P8041
500 V	5P+E (25 A)	01P4051	01P8051
500 V	6P+E (16 A)	01P4061	01P8061

Note: When using two different voltages on the same site, thank you for contacting us.

SOCKET-
OUTLET female
PN7c (16/25 A)
METAL



INLET male
PN7c (16/25 A)
METAL



Umax	Polarity	Part no.	Part no.
50 V	5P (25 A)	09P4050	09P8050
50 V	6P (16 A)	09P4060	09P8060
50 V	7P (16 A)	09P4070	09P8070
415 V	4P+E (25 A)	09P4041	09P8041
415 V	5P+E (25 A)	09P4051	09P8051
415 V	6P+E (16 A)	09P4061	09P8061

BOXESCable gland
not includedWall box
poly 30°Wall box
poly straightWall box
metal straightWall box metal +
inclined metal 45°Wall box poly +
inclined poly 70°

Entry					
M20	01NA053	01NA055	09NA055	09NA653	Not drilled and without cable gland Part no. 51AA058
M25				09NA653418	
M32				09NA653419	

SLEEVESInclined
poly 30°

611A057

Inclined
metal 30°

09NA027

Inclined
poly 70°

51AA757

HANDLES

Straight poly



Angled poly

Straight poly
with poly cable
glandStraight metal
with metal
cable glandStraight poly
without cable
gland with
metric threaded
entry

9-18 mm	01NA013	01NA313	5-12 mm	01NA753	7-13 mm	09NA963	M20	01NA253417
5-21 mm	611A413		8-18 mm	01NA25325P	8-16 mm	09NA95325M	M25	01NA253418
			14-25 mm	01NA25332P	16-24 mm	09NA95332M	M32	01NA253419

**ACCESSORIES & OPTIONS**

Locking with padlock (ø 4 mm) without shaft (padlocks not supplied)

Socket no. + 843



Screw locking imprint BTR 2,5

Socket no. + 22



Reversed interior and contacts (inlet cap is included)

Inlet no. + 001

Socket no. + 001



IP55 self-closing lid (Socket-outlet)

Replace P by S

Eg: 400 V 3P+N+E poly = 01S4017



Inlet cap

01NA126



Self-returning lid

180° opening lid

180° opening and self-returning lid

Socket no. + R

Socket no. + 10

Socket no. + 18