

Specifications for HHP2-30" Fan Size - Horizontal Projection Type

Detailed Specifications


Model		HHP2-30
Fan diameter	in (mm)	30 (762.0)
Air delivery *	cfm (m ³ /hr)	7300 (12403)
Motor power	hp (watts)	1 (746)
Horizontal Projection	on Type wit	h One-Way Louvers
Horizontal air velocity *	fpm (m/s)	1715 (8.7)
Horizontal air throw * †	ft (m)	78 (23.8)
Max. mounting height '	^r † ft (m)	24 (7.3)
Weights and Shipp (wood packaging m	-	imensions a compliance with ISPM No. 15)
Net wt. before adders	lbs (kg)	354 (160.6)
Shipping wt. before add	ders Ibs (kg)	465 (210.9)
Add for flanges	lbs (kg)	16 (7.3)
Crate W X D X H	in	48.25 x 43.0 x 45.9
Crate W X D X H	mm	1225 x 1092 x 1166

* At 70°F (21°C), 60 Hz and sea level.

† The Air throws, Spreads and Max. Mounting heights listed above are based on an air temperature rise (Δ T) of 40°F. To determine these figures for temperature rises other than 40°F, first determine the actual air temperature rise from the performance tables in the brochure, our web based Heater Selection Tool, or factory supplied printouts, and then multiply the respective values by the Correction factor in the table below.

Air Discharge Temperature Correction Factors @ Various Temperature Differences ΔT (°F)								(°F)								
Actual ΔT	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150
Correction	1.24	1.18	1.12	1.06	1.00	0.94	0.88	0.82	0.76	0.7	0.64	0.58	0.51	0.45	0.39	0.33

THORNE & Thorne & Derrick DERRICK +44 (0) 191 410 4292 INTERNATIONAL www.heatingandprocess.com





in the second seco	

