

Data Sheet Ex-Handy 10

DZ2

ATEX



⊕ II 3G Ex ic IIC T4 Gc IP64

⊕ II 3D Ex ic IIIC T120°C Dc

Ambient temperature: -20 °C ≤ Ta ≤ +60 °C

IECEx



Ex ic IIC T4 Gc IP64

Ex ic IIIC T120°C Dc

Ambient temperature: -20 °C ≤ Ta ≤ +60 °C

CSA

(Northern America)



Class I, II, III, Division 2, Groups A-G, T4

CL I, Zone 2 Groups IIC T4

Ex ic IIIC T120°C Dc

Ex ic IIC T4 Gc

Further approvals at: www.ecom-ex.com



Technical Data

Operating System	Android™ 9 Android Zero-Touch Google Play
Processor	Qualcomm Snapdragon MSM8909 platform
Band	Cellular frequency bands: 4G LTE FDD: B1, B2, B3, B4, B5, B7, B8, B11, B12, B13, B20, B21, B25, B26, B28, B66, B71 4G LTE TDD: B38, B39, B40, B41 (2540 Mhz to 2640 Mhz) 3G UMTS: 850 / 900 / 1700 / 1900 / 2100 MHz 2G GSM: 850 / 900 / 1800 / 1900 MHz
Memory	2 GB RAM + 16 GB ROM microSD card up to 128 GB
Display	6,6 cm / (2,6") capacitive multi-touch screen made of extreme shock and scratch resistant Gorilla glass - Support of glove and wet mode - High Visibility in direct sunlight
Ports	- Water-proof magnetic USB 2.0 connector 3.5 mm jack connection with special ecom mounting solution
Dimensions	148 x 67 x 24 mm
Weight	approx. 330 g
Dedicated keys	Programmable key / Alarm / Power / Multifunction / Volume / Hardware buttons for Android features
Connectivity	4G / LTE -standard (SIM unlocked and free); Nano SIM - WiFi 802.11 a/b/g/n/e/k/r/h; 2.4 Ghz and 5 Ghz support - Bluetooth® 4.2 incl. BLE (Bluetooth Low Energy) - GPS / A-GPS / Glonass / Beidou - NFC
Camera	8 MP rear camera with auto focus (optional) and LED flash with torchlight function
Battery	4400 mAh
Protection	IP68, MIL-STD-810G